



# Wireless Presentation System WPS100



Wirelessly Share a Display or Projector

## Advanced Features

**30**

*fps*

**HDMI**

*output*

**WiFi**

*AP-Client  
mode*

**SNMP**

*Manager*

**DirectX**

*Support*

The WPS100 connects a display or projector to up to 20 wireless devices. You can switch between them and display up to 4 devices on screen effortlessly.



HUB USB Dongle



**WPS100**  
WPS100 intercepts wireless devices and projects to the screen

Supports: PC, Smartphone, Mac, PDA & other wireless devices

### Features - WPS100

- Wifi AP-Client mode allows WPS100 to join existing WiFi Access Points wirelessly.
- SNMP Manager allows multiple WPS100 device(s) to be configured through friendly SNMP applications
- Windows DirectX application projection supports DirectX application projections, such as AutoCAD, ProE and 3D PC games
- Plug-and-show (PnS) Driverless Install
- 4-to-1 Split Screen Projection
- Near Real-time Network Screen and Audio Projection
- Conference Control
- Changeable Customized Image of Standby Splash Screen
- Multiple User Access
- Web management including software download and device settings
- Session Login Code, WEP/WPA key, and GateKeeper setting for security purpose
- Windows Mobile Smartphone Wireless Projections (MobiShow)
- Wireless Access Point usage (802.11n)
- Equipped with RJ-45 port for wired LAN links which allows users to browse Internet



**Windows 7  
Vista  
XP  
Mac  
Mobile 6.5**

**30**  
fps

**HDMI**  
output

**WiFi**  
AP-Client  
mode

**SNMP**  
Manager

**DirectX**  
Support

### Specifications - WPS100

Standards	IEEE 802.11b/g/n 2.4GHz IEEE 802.3(10BASE-T)/IEEE 802.3u(100BASE-TX)
Managements:	Web-based configuration, SNMP
Security	IEEE Standard 64/128 bit WEP/WPA/WPA2-PSK
Supported Output Resolutions	VGA: SVGA (800x600) / XGA (1024x768) / WXGA(1280x768) / WXGA+(1280x800) HDMI: 720p (1280x720)
Supported Windows Account Right	Administrators, Limited User, Guest
Supported Operation System	Windows XP/Vista/7, Windows Mobile 5.0 and above, Mac OS X 10.5 & 10.6
Power	External Power adaptor 5V DC input 2.6A
Interface	15Pin VGA HDMI RJ-45 Reset Button Stereo Phone Jack
Mechanical	Dimension: 150 x 75 x 22 mm Weight: 257g
Certificate	FCC/CE
Warranty	1 year
Shipping Information	Dimension: 8.75" x 8.25" x 2.5", Weight: 1.75 LBS

### Outputs

