



INTERACTIVE DISPLAY

simpleboard[™] j

4K | Modular | Simplified Setup


For spaces where clarity, flexibility and ease matter most.

basic on purpose.

SimpleBoard j is built for **simplicity and flexibility across rooms**.

With **no built-in operating system**, it works with the platform your organization chooses—making it easier to **standardize setups** and keep everyone aligned.

With **fewer built-in components to manage**, it's easier for IT teams to support and maintain, delivering a reliable experience every time.



Learn more about the BundleBoard i at
qomo.com/simpleboard-j or scan the QR code.



simpleboard™ j		65"	75"	86"
Model		QITSB65 j	QITSB75 j	QITSB86 j
Display Parameter	DLED	●	●	●
Backlight	OPS Options	●	●	●
Aspect Ratio	16:9	●	●	●
Resolution	4K	●	●	●
Infrared Touch	40 Points	●	●	●
Glass Type	≥9H heat-tempered, Anti-glare, Zero Bonded	●	●	●
Brightness	450cd/m²	●	●	●
Life Time	≥50,000 hrs	●	●	●
Response Time	≤5ms	●	●	●
Speakers	Front-Facing 2 × 20W	●	●	●
Operating System	None	●	●	●
Compatible Operating Systems	Windows, Mac, Chrome, Linux	●	●	●
OPS Options	i5 8 GB or i7 16 GB Windows OPS, Chrome Flex OPS, Android EDLA OPS	●	●	●
Power				
Power Requirements	AC 100 V ~ 240 V, 50/60 Hz	●	●	●
Power Consumption Without OPS		330W	395W	470W
Standby Condition	<0.5W	●	●	●
Physical Specs				
VESA	4-M8 Screw Hole 600 mm × 400 mm	●	●	●
Dimensions (LxWxH)	L×W×D	1483.9 mm × 87.4 mm × 891.2 mm	1705 mm × 87.6 mm × 1015.7 mm	1950.4 mm × 87.6 mm × 1153.7 mm
Packing Dimensions L*W*H	L×W×H	1640 mm × 185 mm × 1010 mm	1860 mm × 185 mm × 1125 mm	2095 mm × 185 mm × 1265 mm
Housing Material	Aluminum/Metal plate	●	●	●
Ports	1*USB-C, 4*USB 3.0, 1*USB 2.0, 1*Touch-USB-A 3.0, 1*Touch-USB-B 2.0, 3*HDMI IN, 1*DP IN, 2*LAN, 1*RS232 IN, 1*OPS, 1*Audio IN, 1*Audio OUT, 1*VGA IN			