



# simpleboard™ j

4K | Modular | Simplified Setup  
For spaces where clarity, flexibility and ease matter most.

basic on purpose.

SimpleBoard j is built for simplicity and flexibility across rooms.

With **no built-in operating system**, it works with the platform your organization chooses—making it easier to **standardize setups** and keep everyone aligned. With **fewer built-in components to manage**, it's easier for IT teams to support and maintain, delivering a reliable experience every time.



Learn more about the SimpleBoard j at  
[qomo.com/simpleboard-j](https://qomo.com/simpleboard-j) or scan the QR code.



simpleboard™ j		65"	75"	86"
----------------	--	-----	-----	-----

Model		QITSB65 j	QITSB75 j	QITSB86 j
Resolution	4K	●	●	●
Aspect Ratio	16:9	●	●	●
Infrared Touch	40 Points	●	●	●
Glass Type	≥9H heat-tempered, Anti-glare, Zero Bonded	●	●	●
Brightness	450cd/m²	●	●	●
Life Time	≥50,000 hrs	●	●	●
Response Time	≤5ms	●	●	●
Speakers	Front-Facing 2 × 20W	●	●	●
Operating System	None	●	●	●
OPS Options	i5 8 GB or i7 16 GB Windows OPS, Chrome Flex OPS, Android EDLA OPS	●	●	●

**Annotation** Optional Annotate Over Any Input

**Power**

Power Requirements	AC 100 V ~ 240 V, 50/60 Hz	●	●	●
Power Consumption Without OPS		330W	395W	470W
Standby Condition	<0.5W	●	●	●

**Physical Specs**

VESA		VESA: 65" :400X600, 75":400x800, 86": 600x800		
Dimensions (LxWxH)	L×W×D	1483.9 x 87.4 x 891.2 mm	1705 x 87.6 x 1015.7 mm	1950.4 x 87.6 x 1153.7 mm
Packing Dimensions L*W*H	L×W×H	1640 x 185 x 1010 mm	1860 x 185 x 1125 mm	2095 x 185 x 1265 mm
Housing Material	Aluminum/Metal plate	●	●	●
Ports		1*USB-C, 4*USB 3.0, 1*USB 2.0, 1*Touch-USB-A 3.0, 1*Touch-USB-B 2.0, 3*HDMI IN, 1*DP IN, 2*LAN, 1*RS232 IN, 1*OPS, 1*Audio IN, 1*Audio OUT, 1*VGA IN		

**Accessories** Remote Controller, Pens x 2, 3M Power Cord, 3 M USB A-B Cable, 3M HDMI Cable, Wall mount